

# System concept

Whether in boutiques and retail shops, hair-dresser's shops or restaurants and cafés: The discreet design and the compact dimensions make the POS S14 the perfect solution for almost any ambience.

The capacitive touch screen can be controlled via intuitive swipe gestures and is extremely scratchproof and resistant. The wide format display with a diagonal of 14.1" allows many functions to be displayed without scrolling, making operation of the POS system convenient and efficient. The powerful processor also ensures fast processing and display of POS data.



# Hardware

Technical data of the Duratec S14 POS system	
Display diagonal	35.8 cm (14.1")
Display type	TFT-LCD
Display lighting	LED backlight
Display size (active)	30.86 x 17.32 cm
Display resolution	1366 x 768 Pixel
Colours	up to 262,144
Input	Touch screen (projective-capacitive)
Housing	black ABS plastic housing
Processor	i.MX 6DualLite, 1GHz
Main memory	1 GB DDR3
Mass storage	8 GB eMMC
Network	10/100/1000 Base-T; Ethernet Network support available as of software version D/A/CH Gastro 1.4.0.0. The use of the Duratec MobileApp as mobile order terminal requires additional licences. Maximum number of supported MobileApp devices per network: 5
USB ports	4x USB 2.0; port type A
Serial ports	4x RS232; port type RJ45; for external devices
Cash drawer ports	RJ12-port for connection of a cash drawer
MicroSD card slot	for MicroSD cards



Technical data of the Duratec S14 POS system	
<b>SIM-card slot</b>	for standard Mini-SIM cards (25 x 15 mm)
<b>Power supply</b>	via external power supply; installation in stand possible
<b>Micro-USB slot</b>	for service purposes
<b>Power consumption</b>	13 W maximum 11 W in normal mode without external appliances 0.4 W in standby mode
<b>Temperature</b>	storage: -20 to 60 °C operation: 0 to 35 °C
<b>Dimensions (W x H x D)</b>	see drawings
<b>Weight</b>	ca. 3.25 kg
<b>Certified</b>	CE, FCC Class A

Technical data of the power supply Duratec POS S14	
<b>Input voltage</b>	100 to 240 V alternating voltage
<b>Output voltage</b>	+ 24 V direct voltage
<b>Output current</b>	max. 3.75 A
<b>Output power</b>	max. 90 W
<b>Power consumption</b>	max. 93 W
<b>No-load loss</b>	0.3 to 0.5 W
<b>Temperature</b>	storage: -20 to 80 °C operation: 0 to 40 °C
<b>Air humidity</b>	operation: 20 to 80 %, non condensing
<b>Dimensions (W x H x D)</b>	140,1 x 65,1 x 25,4 mm
<b>Weight</b>	360 g
<b>Certified</b>	CE, UL 60950-1

## Software

Version for companies from the catering trade	
<b>Most important functions</b>	Clearly arranged function keys, to be allocated by operator group
	Orders on guest check
	Automatic side dish enquiry
	Happy hour prices
	Different price levels
	Various discounts
	Table split
	Adjustable operator rights
	Reporting
	Backup function
<b>bonVito (optional integrated marketing module)</b>	Coupon and discount campaigns, customer vouchers, stamps, table reservations, customer cards

# Scope of delivery

Duratec POS S14	
<b>Standard shipment</b>	Duratec POS S14 system
	Power supply unit
	Mains cable
	Duratec POS software with licence
	Security and installation instructions
<b>Optional accessories</b>	Dispatch box
	Customer display Duratec S14 Operator lock Duratec S14

# Dimensions (in mm and inch)

