

DURATEC

### System concept

The Duratec POS S15 combines security, efficiency and flexibility with ease of operation and programming at an extremely reasonable price, making it the ideal stationary POS system solution for small to medium-sized companies.

Print of receipts for entertainment expenses with automatic address query and intuitive guest check split- and transfer functions are but a few of the numerous field-proven functions that guarantee safe and efficient procedures.

Three prices per PLU, PLUs with free price input, happy hour- or ingredients functions provide you with the required flexibility to react to different customer groups and customer requests.

#### Hardware

Technical data of Duratec POS S15 POS system		
Display diagonal	38.1 cm (15")	
Display type	TFT-LCD	
Display backlight	CCFL backlight	
Display size (active)	30.4 x 22.8 cm	
Display resolution	1024 x 768 pixel	
Colours	up to 65,536	
Input	analog-resistive 5-wire touch screen	
Housing	black powder-coated full metal housing	
Stand	black; powder-coated aluminium	
Processor	Marvell ARMADA 168, 1066 MHz	
Main memory	512 MB DDR2-RAM	
Cache	1 MB SRAM	
Mass memory	4 GB Flash memory	
Network	10/100BASE-T; Ethernet Network support presumably available as of software version UK Gastro 1.3.0.0. The use of the Duratec MobileApp as mobile order terminal requires additional licences. Maximum number of support- ed MobileApp devices per network: 5	
USB ports	8x USB 2.0; type A; 2 of which at the left side	
Serial ports	6x RS232; type RJ45; for additional devices	
Cash drawer ports	RJ12 for connection of one cash drawer	
Audio socket	3.5 mm jack; stereo; for loudspeaker	
Operator socket	3.5 mm jack; for Duratec L20 lock system	
SD-card slot	for SD-cards up to 4 GB and SDHC-cards up to 32 GB	



Made in Germany © Vectron Systems AG Current as of 02/2017 Subject to error and technical modification.



Technical data of Duratec POS S15 POS system		
SIM-card slot	for standard Mini SIM-cards (25 x 15 mm) - as of device revision 1.11	
Loudspeaker	mono; 2 W	
Power supply	through external power supply PS61; integrated in stand	
Buffer battery	for permanent power supply of the cache	
Power consumption	18 W in normal operation without external devices 0.4 W in standby	
Temperature	storage: -10 to 50 °C operation: 0 to 40 °C	
Dimensions (W x H x D)	see drawings	
Weight	approx. 9.5 kg	
Certified	CE	

	Technical data of power supply PS61
Input voltage	100 to 240 V alternating voltage
Output voltage	+ 24 V direct current
Output current	max. 3.75 A
Output power	max. 90 W
Power consumption	max. 93 W
No-load loss	0.3 to 0.5 W
Temperature	storage: -40 bis 85 °C operation: 0 bis 40 °C
Air humidity	operation: 5 to 95 %, non condensing
Dimensions (W x H x D)	145 x 60 x 32 mm
Weight	450 g
Certified	CE, UL 60950-1

### Software

	Technical data of Duratec POS software
PLUs	2,000
Departments	90
Prices	3 (normal price, staff price, happy hour price)
Operators	50
Guest check memory	200
POS systems per network	6
Printers per network	5
Scope of functions	Sort groups for three courses
	Intuitive PLU selection via button levels
	Three levels for fast moving consumer goods
	Staff price
	Happy hour function



Made in Germany © Vectron Systems AG Current as of 02/2017 Subject to error and technical modification.



Technical data of Duratec POS software	
Scope of functions	Print of receipt for entertainment expenses with automatic address
	query
	VIP sale
	Eight media
	Tip function
	Three discount types (single discount in %, discount on invoice total in %, absolute discount)
	Invoice memory for the last 200 invoices
bonVito	unrestricted support of the bonVito online marketing tool (liable to costs - more information and prices at www.bonvito.net)

## Shipment

Duratec POS S15		
Standard shipment	Duratec POS S15 POS system	
	Operator lock Duratec L21 with four operator keys	
	5 port covers (one port cover for the whole ports bracket; two covers for the SD-card- and SIM-card slot)	
	Stand S50	
	Power supply PS61	
	Power cord	
	Duratec POS software with licence	
	Notes on safety and installation	
	Dispatch box	
Optional accessories	VESA wall mount	





# Dimensions (in mm and inch)





